

## Americans with Disabilities Act Ramp Guidelines

Ramps are required for any change in level greater than  $\frac{1}{2}$  inch.

Ramps have a maximum slope of 1:12 (4.8 degrees).

Ramps have a minimum width of 36 inches.

There must be a minimum 5 feet by 5 feet flat area at the top and bottom of the ramp for turning.

Ramps may be no longer than 30 feet horizontally between flat rest or turn platforms.

Source: [https://www.access-board.gov/aba/ufas.html#4.8.2\\*-slope-and-rise](https://www.access-board.gov/aba/ufas.html#4.8.2*-slope-and-rise)

## Americans with Disabilities Act Ramp Guidelines

Ramps are required for any change in level greater than  $\frac{1}{2}$  inch.

Ramps have a maximum slope of 1:12 (4.8 degrees).

Ramps have a minimum width of 36 inches.

There must be a minimum 5 feet by 5 feet flat area at the top and bottom of the ramp for turning.

Ramps may be no longer than 30 feet horizontally between flat rest or turn platforms.

Source: [https://www.access-board.gov/aba/ufas.html#4.8.2\\*-slope-and-rise](https://www.access-board.gov/aba/ufas.html#4.8.2*-slope-and-rise)

## Americans with Disabilities Act Ramp Guidelines

Ramps are required for any change in level greater than  $\frac{1}{2}$  inch.

Ramps have a maximum slope of 1:12 (4.8 degrees).

Ramps have a minimum width of 36 inches.

There must be a minimum 5 feet by 5 feet flat area at the top and bottom of the ramp for turning.

Ramps may be no longer than 30 feet horizontally between flat rest or turn platforms.

Source: [https://www.access-board.gov/aba/ufas.html#4.8.2\\*-slope-and-rise](https://www.access-board.gov/aba/ufas.html#4.8.2*-slope-and-rise)